



DIMENSIONS AND QUANTITIES FOR TOP SLAB

M.H. Dia. "D"	M.H. Dia. "E"	1/2" # Steel Reinforcement Bars														Weight Steel lbs.	Approx Concrete Volume Cu. Yd.
		A1		A2		A3		A4		A5		A6					
		No.	Length	Rod	No.	Length	Rod	No.	Length	No.	Length	No.	Length				
4'-0"	4'-10"	2	17'-5"	2'-3"	2	9'-0"	1'-2"	3	5'-11"	3	5'-3"	2	6'-6"	-	--	66	.38
5'-0"	6'-10"	2	20'-6"	2'-10"	2	9'-0"	1'-2"	3	7'-2"	3	6'-8"	2	7'-8"	1	7'-6"	82	.63

APPROVED 6-27-07

Brad Fagell
CITY ENGINEER

REVISED: 21 JUN 07

CAST-IN-PLACE
CONCRETE TOP SLAB
FOR SHALLOW
MANHOLES

PERVIOUSLY 002 A5

CITY OF LANCASTER, OHIO
DEPARTMENT OF ENGINEERING

STANDARD
CONSTRUCTION DRAWING

DWG. BY: BIC
CHK'D BY: *DPK*

FILE NUMBER

S-10